



> DOWN-CONDUCTORS AND ACCESSORIES

> CLIPS FOR TAPES

> TAPE BUCKLE CLIP


Down-conductor holder suitable for fixing 30 x 2 or 30 x 3.5 mm tape to flat surface. The AT-006E and AT-061E include suitable screws and neoprene washers for metal sheets or sandwich panels. AT-012E and AT-019E include self-drill double screws and neoprene washers for metal structures. AT-216E and AT-217E are designed to overcome obstacles such as cornices.

Reference	Dimensions (mm)	Tape range (mm)	Conductor elevation (mm)	Includes	Material	Weight (g)
AT-240E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Plug and lag bolt M6 x 25 mm	Stainless steel	115
AT-006E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Self-drill screw + neoprene washer	Stainless steel	115
AT-012E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Self-drill double screw and neoprene washer	Stainless steel	120
AT-241E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Plug and lag bolt M6 x 25 mm	Galvanized steel	115
AT-061E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Self-drill screw + neoprene washer	Galvanized steel	115
AT-019E	58 x 13 x 20	30 x 2 - 30 x 3.5	8	Self-drill double screw and neoprene washer	Galvanized steel	120
AT-216E	58 x 63 x 20	30 x 2 - 30 x 3.5	58	Plug and lag bolt M8 x 40 mm	Stainless steel + Naval brass	290
AT-217E	58 x 113 x 20	30 x 2 - 30 x 3.5	108	Plug and lag bolt M8 x 40 mm	Stainless steel + Naval brass	485

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561



APPLICATION AT-240E



APPLICATION AT-006E



AT-240E (SS - stainless steel)

AT-241E (GS - galvanized steel)