



> DOWN-CONDUCTORS AND ACCESSORIES

> CONDUCTORS

> BARE COPPER TAPE

Copper tape recommended as a down-conductor for lightning protection systems.

Reference	Dimensions (mm)	Weight per metre (kg/m)
AT-006D	12.5 x 1.5	0.20
AT-007D	12.5 x 3	0.30
AT-008D	20 x 1.5	0.25
AT-009D	20 x 3	0.32
AT-010D	25 x 1.5	0.35
AT-011D	25 x 3	0.70
AT-012D	25 x 4	0.90
AT-013D	25 x 6	1.35
AT-014D	30 x 2	0.50
AT-015D	30 x 3	0.80
AT-016D	30 x 4	1.10
AT-017D	30 x 5	1.40
AT-018D	38 x 3	1.00
AT-019D	38 x 5	1.70
AT-020D	38 x 6	1.80
AT-021D	40 x 3	1.10
AT-022D	40 x 4	1.40
AT-023D	40 x 5	1.80
AT-024D	40 x 6	2.20
AT-025D	50 x 3	1.40
AT-026D	50 x 4	1.80
AT-027D	50 x 5	2.20
AT-028D	50 x 6	2.75

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561

Other dimensions, please contact us



AT-011D