



> DOWN-CONDUCTORS AND ACCESSORIES


> CLAMPS

> STRAIGHT CLAMP

Linear joint for cable or round conductor.

Reference	Dimensions (mm)	Conductor range			Rod	Material	Weight (g)
		Ø (mm)	mm ²	Tape (mm)			
AT-015F	Ø21 x 100	8 - 10	50 - 70	-	-	Naval brass	140
AT-116F	Ø15 x 75	6 - 8	25 - 50	-	-	Copper	140
AT-117F	Ø15 x 75	6 - 8	25 - 50	-	-	Stainless steel	140
AT-118F	60 x 27 x 20	8	50	-	-	Galvanized steel	140
AT-135F	60 x 27 x 20	8	50	-	-	Gunmetal	100
AT-105F	40 x 30 x 17	8 - 10	50 - 70	-	-	Aluminium	50
AT-135J	43 x 41 x 30	7 - 10	35 - 70	-	16	Galvanized steel	120
AT-090H	85 x 41 x 44	8 - 10	50 - 70	30 x 2 - 30 x 3.5	20	Naval brass	265

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561



AT-015F (NB - naval brass)
AT-116F (Cu - copper)
AT-117F (SS - stainless steel)



AT-090H



APPLICATION AT-090H



APPLICATION AT-135J



APPLICATION AT-105F



APPLICATION AT-118F (GS - galvanized steel)
AT-135F (Gu - gunmetal)