



> DOWN-CONDUCTORS AND ACCESSORIES

> CLIPS FOR CABLE

> NYLON HOLD-FAST CABLE CLIP

Nylon clip to secure round conductor or cable.

Reference	Dimensions (mm)	Conductor range		Conductor elevation (mm)	Includes	Material	Weight (g)
		Ø (mm)	mm ²				
AT-020E	25 x 25 x 35	8 - 10	50 -70	18	Plug and lag bolt M6 x 25 mm	Nylon	9
AT-034E	25 x 25 x 35	10	70	18	Plug and lag bolt M6 x 25 mm	Nylon	9
AT-035E	25 x 25 x 35	8	50	25	Plug and lag bolt M6 x 25 mm	Nylon	10
AT-036E	25 x 25 x 35	10	70	25	Plug and lag bolt M6 x 25 mm	Nylon	10
AT-037E	25 x 25 x 70	8	50	40	Plug and lag bolt M6 x 25 mm	Nylon	11
AT-038E	25 x 25 x 70	10	70	40	Plug and lag bolt M6 x 25 mm	Nylon	13
AT-021E	25 x 25 x 90	8	50	18	Integrated plug and screw	Nylon	10
AT-039E	25 x 25 x 90	10	70	18	Integrated plug and screw	Nylon	10
AT-022E	25 x 25 x 80	8	50	25	Anti-humidity plug and screw	Nylon	20

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561



APPLICATION AT-021E



APPLICATION AT-035E



APPLICATION AT-022E



APPLICATION AT-037E



APPLICATION AT-020E