



## &gt; INTERCEPTION SYSTEMS AND ACCESSORIES


## &gt; FIXINGS

## &gt; FLAT SADDLE

Used for supporting lightning conductor air terminals on the flat roof and connecting to the cable or round.

| Reference | Dimensions (mm) | Conductor range |                 | Thread | Material        | Weight (g) |
|-----------|-----------------|-----------------|-----------------|--------|-----------------|------------|
|           |                 | Ø (mm)          | mm <sup>2</sup> |        |                 |            |
| AT-112B   | 85 x 85 x 64    | 8               | 50              | M16    | Gunmetal        | 1030       |
| AT-113B   | 85 x 85 x 64    | 10              | 70              | M16    | Gunmetal        | 950        |
| AT-114B   | 85 x 85 x 64    | 13              | 95              | M16    | Gunmetal        | 950        |
| AT-093B   | 79 x 79 x 20    | 8 - 13          | 50 - 95         | M16    | Aluminium       | 160        |
| AT-124B   | 30 x 34 x 57    | 8 - 10          | 50 - 70         | M16    | Stainless steel | 170        |
| AT-125B   | 30 x 34 x 57    | 8 - 10          | 50 - 70         | M20    | Stainless steel | 170        |

Complies with IEC 62305, IEC 62561, BS EN 1982



AT-114B