




> IGA TEST series

> IGA TEST T

Three-phase protector against permanent overvoltages with integrated miniature circuit breaker





IGA TEST series protectors cut off the power supply when they detect a permanent overvoltage (for example, a fault in the neutral), thus protecting the equipment installed downstream.

To restore the main circuit breaker, it is necessary to reconnect the protective coils in advance using the RESET buttons. Reclosing will always be carried out from the most external coil to the one closest to the MCB.

IGA TEST permanent overvoltage protectors can be used together with ATSUB-D transient overvoltage protectors.

The integrated MCB is available for the most usual nominal currents: 6, 10, 16, 20, 25, 32, 40, 50 and 63 A.

> INSTALLATION

They must be installed **in series** with the low voltage line, between the power control circuit breaker (ICP) and the residual current device (ID).

Installation should be carried out without power running through the line.

The protective coils are to be installed between the lines connected to the residual current breaker and the neutral.

The protector is formed by protective coils for permanent overvoltage linked to a miniature circuit breaker (MCB).

Reference:		IGA TEST T 6 AT-9055	IGA TEST T 10 AT-9056	IGA TEST T 16 AT-9057	IGA TEST T 20 AT-9058	IGA TEST T 25 AT-9006	IGA TEST T 32 AT-9007	IGA TEST T 40 AT-9008	IGA TEST T 50 AT-9009	IGA TEST T 63 AT-9010
Nominal current:		6 A	10 A	16 A	20 A	25 A	32 A	40 A	50 A	63 A
Nominal voltage:	Un	230 V _{AC}								
Maximum overvoltage:		400 V _{AC}								
Actuation voltage:	Ua	265 - 280 V _{AC}								
Actuation time:		@275 V _{AC} + 8 - 10 s / @400 V _{AC} + 0.1 - 0.2 s								
Maximum short-circuit current:		6 kA								
Dimensions:		123 x 81 x 65 mm (7 modules DIN 43880)								
MCB cable range:		Minimum / Maximum section: 1.5 / 25 mm ²								
Coil cable range:		Minimum / Maximum section: 1.5 / 2.5 mm ² (single-stranded) or 4 mm ² (multi-stranded)								
Tests certified according to standards: UNE-EN 50550, UNE-EN 60898										

> TECHNICAL DATASHEET