



> DOWN-CONDUCTORS AND ACCESSORIES

> TEST CLAMPS

> CABLE AND TAPE TEST CLAMP

Especially used for disconnection and testing purposes for cable, round or tape conductors.


Reference	Dimensions (mm)	Conductor range			Includes	Material	Weight (g)
		Ø (mm)	mm ²	Tape (mm)			
AT-010F	55 x 30 x 75	8	50	30 x 2 - 30 x 3.5	Plug and screw M4 x 38	Naval brass	295
AT-086F	30 x 65 x 45	7	35	25 x 3	-	Gunmetal	400
AT-087F	30 x 65 x 45	8	50	25 x 3	-	Gunmetal	400
AT-088F	30 x 65 x 45	10	70	25 x 3	-	Gunmetal	400
AT-089F	30 x 65 x 45	13	95	25 x 3	-	Gunmetal	390
AT-090F	30 x 65 x 45	15	120	25 x 3	-	Gunmetal	390
AT-091F	30 x 65 x 45	8	50	25 x 3	-	Aluminium	90
AT-095F	55 x 75 x 20	8 - 10	50 - 70	30 x 3.5	Plug and screw M4 x 38	Nickel plated brass	500

Complies with IEC 62305, UNE 21186, NF C 17-102, IEC 62305, IEC 62561



AT-010F

APPLICATION AT-010F



APPLICATION AT-095F



APPLICATION AT-086F (Gu - gunmetal) 
AT-091F (Al - aluminium) 

