



> INTERCEPTION SYSTEMS AND ACCESSORIES

> MASTS AND ANCHORAGES

> U-SHAPED ANCHORAGE

1" - 1½" mast anchorage to be embedded or screwed into the wall. The 60 cm U-shaped anchorages are designed to avoid obstacles such as cornices of up to 50 cm. The anchorages need a minimum of 60 cm between each other and at least 30 cm from the top of the wall in order to ensure correct attachment. Single extra supports, ref: AT-012B, AT-015B, AT-009B, AT-021B and AT-025B, respectively.



AT-013B

Reference	Model	Dimensions (mm)	Includes	Material	Weight (kg)
AT-013B	30 cm U-shaped anchorage embedded into the wall	2 x (50 x 340 x 390)	2 supports	Galvanized steel	4.6
AT-014B	30 cm U-shaped anchorage embedded into the wall	3 x (50 x 340 x 390)	3 supports	Galvanized steel	6.9
AT-016B	60 cm U-shaped anchorage embedded into the wall	2 x (50 x 640 x 615)	2 supports	Galvanized steel	11.0
AT-017B	60 cm U-shaped anchorage embedded into the wall	3 x (50 x 640 x 615)	3 supports	Galvanized steel	16.0
AT-010B	15 cm U-shaped anchorage screwed into the wall	2 x (50 x 400 x 140)	2 supports	Galvanized steel	4.5
AT-011B	15 cm U-shaped anchorage screwed into the wall	3 x (50 x 400 x 140)	3 supports	Galvanized steel	6.8
AT-023B	30 cm U-shaped anchorage screwed into the wall	2 x (50 x 400 x 290)	2 supports	Galvanized steel	6.0
AT-024B	30 cm U-shaped anchorage screwed into the wall	3 x (50 x 400 x 290)	3 supports	Galvanized steel	9.0
AT-026B	60 cm U-shaped anchorage screwed into the wall	2 x (50 x 600 x 670)	2 supports	Galvanized steel	10.0
AT-027B	60 cm U-shaped anchorage screwed into the wall	3 x (50 x 600 x 670)	3 supports	Galvanized steel	15.0

Complies with UNE 21186, NF C 17-102



AT-023B



APPLICATION AT-013B



APPLICATION AT-023B