



> INTERCEPTION SYSTEMS AND ACCESSORIES

> RODS AND MESHED CONDUCTORS

> AIR TERMINATION ROD

Ø20 mm rods are assembled for example with accessories such as AT-022F or AT-003M (tables 27, 28), except AT-023A and AT-019A which are assembled, for example, with AT-010A (table 15). Ø16 mm rods are assembled with AT-161A (table 15) or AT-124B (table 18).

Reference	Dimensions (mm)	Thread	Material	Weight (kg)
AT-053L	Ø20 x 300	M10 female thread	Stainless steel	0.65
AT-055L	Ø20 x 500	M10 female thread	Stainless steel	1.14
AT-096A	Ø20 x 1000	M10 female thread	Stainless steel	2.35
AT-097A	Ø20 x 300	M10 female thread	Chrome-plated copper	0.70
AT-098A	Ø20 x 500	M10 female thread	Chrome-plated copper	1.25
AT-099A	Ø20 x 1000	M10 female thread	Chrome-plated copper	2.60
AT-023A	Ø20 x 400	M20	Stainless steel	0.90
AT-019A	Ø20 x 400	M20	Chrome-plated copper	1.00
AT-121A	Ø16 x 300	M16	Stainless steel	0.50
AT-122A	Ø16 x 600	M16	Stainless steel	1.00

Complies with IEC 62305, IEC 62561



AT-023A (SS - stainless steel)
AT-019A (CC - Chrome-plated copper)

AT-053L (SS - stainless steel)
AT-097A (CC - Chrome-plated copper)