



> INTERCEPTION SYSTEMS AND ACCESSORIES

> RODS AND MESHED CONDUCTORS

> AIR TERMINAL WITH MAST

For use in conjunction with reduced anchorages as AT-107B (table 24) or mast anchorages (tables 31 to 41). AT-024A and AT-017A include an adapting piece AT-011A (table 15) for fixing the conductor (tape, cable or round) inside the mast. The rest of the references require the conductor to be fixed on the outside of the mast (For example AT-033A, table 64). A conductor clip is included in reduced anchorage AT-107B.

Reference	Dimensions (mm)	Total height (m)	Material	Weight (kg)
AT-013A	Ø20 x 400 + Mast Ø1" x 1000	1.4	Stainless steel / Stainless steel (mast)	2.5
AT-014A	Ø20 x 400 + Mast Ø1" x 2000	2.4	Stainless steel / Stainless steel (mast)	4.5
AT-024A	Ø20 x 400 + Mast Ø1½" x 2000	2.4	Stainless steel / Galvanized steel (mast)	8.3
AT-015A	Ø20 x 400 + Mast Ø1" x 1000	1.4	Chrome-plated copper / Stainless steel (mast)	2.6
AT-016A	Ø20 x 400 + Mast Ø1" x 2000	2.4	Chrome-plated copper / Stainless steel (mast)	4.6
AT-017A	Ø20 x 400 + Mast Ø1½" x 2000	2.4	Chrome-plated copper / Galvanized steel (mast)	8.4

Complies with IEC 62305, IEC 62561

- AT-024A (SS - stainless steel)
- AT-017A (CC - Chrome-plated copper)

