



> INTERCEPTION SYSTEMS AND ACCESSORIES

> RODS AND MESHED CONDUCTORS

> LIGHTNING ROD FOR WEDGE



AT-045A

Non-threaded lightning rods suitable for use with stackable wedge concrete bases (for example AT-030B, table 29).

Reference	Dimensions (mm)	Total height (m)	Material	Weight (kg)
AT-025A	Ø16 x 750	0.75	Galvanized steel	1.22
AT-026A	Ø16 x 1000	1	Galvanized steel	1.60
AT-027A	Ø16 x 1250	1.25	Galvanized steel	2.00
AT-028A	Ø16 x 1500	1.50	Galvanized steel	2.40
AT-029A	Ø16 x 2000	2	Galvanized steel	3.20
AT-030A	Ø16 x 2500	2.50	Galvanized steel	4.20
AT-031A	Ø16 x 3000	3	Galvanized steel	4.80
AT-032A	Ø16 x 1000	1	Stainless steel	1.60
AT-034A	Ø16 x 1500	1.50	Stainless steel	2.38
AT-035A	Ø16 x 2000	2	Stainless steel	3.20
AT-036A	Ø16 x 1000	1	Copper	1.85
AT-037A	Ø16 x 1500	1.50	Copper	2.77
AT-038A	Ø16 x 1000	1	Aluminium	0.54
AT-039A	Ø16 x 1500	1.50	Aluminium	0.82
AT-040A	Ø16 x 2000	2	Aluminium	1.80
AT-041A	Ø16 x 2500	2.50	Aluminium	1.40
AT-042A	Ø16 x 3000	3	Aluminium	1.68
AT-043A	Ø10 x 1000	1	Aluminium	0.22
AT-044A	Ø16 x 500 + Ø10 x 1000	1.50	Aluminium	0.48
AT-045A	Ø16 x 1000 + Ø10 x 1000	2	Aluminium	0.76
AT-046A	Ø16 x 1500 + Ø10 x 1000	2.50	Aluminium	1.02
AT-047A	Ø16 x 2000 + Ø10 x 1000	3	Aluminium	1.30

Complies with IEC 62305, IEC 62561

- AT-026A (GS - galvanized steel)
- AT-032A (SS - stainless steel)
- AT-036A (Cu - copper)
- AT-038A (Al - aluminium)