



> INTERCEPTION SYSTEMS AND ACCESSORIES

> MASTS AND ANCHORAGES

> ANGLE BAR ANCHORAGE

1" - 1½" mast anchorage to be welded to metal structures.

The anchorages require a minimum of 60 cm between each other in order to ensure they are correctly fixed. Single extra supports, ref: AT-034B, AT-044B, AT-037B and AT-047B, respectively.

Reference	Model	Dimensions (mm)	Includes	Material	Weight (kg)
AT-035B	30 cm angle bar anchorage	2 x (50 x 120 x 300)	2 supports	Galvanized steel	4.0
AT-036B	30 cm angle bar anchorage	3 x (50 x 120 x 300)	3 supports	Galvanized steel	5.5
AT-045B	30 cm angle bar anchorage	2 x (50 x 120 x 300)	2 supports	Stainless steel	3.0
AT-046B	30 cm angle bar anchorage	3 x (50 x 120 x 300)	3 supports	Stainless steel	4.5
AT-038B	60 cm angle bar anchorage	2 x (50 x 120 x 600)	2 supports	Galvanized steel	6.0
AT-039B	60 cm angle bar anchorage	3 x (50 x 120 x 600)	3 supports	Galvanized steel	9.0
AT-048B	60 cm angle bar anchorage	2 x (50 x 120 x 600)	2 supports	Stainless steel	4.5
AT-049B	60 cm angle bar anchorage	3 x (50 x 120 x 600)	3 supports	Stainless steel	7.0

Complies with UNE 21186, NF C 17-102



■ AT-038B (GS - galvanized steel)
■ AT-048B (SS - stainless steel)



APPLICATION AT-038B