



> EQUIPOTENTIAL BONDING

> EARTH BARS



AT-053J



AT-055J




AT-054J (Cu - copper)
AT-116J (SS - Stainless steel)



AT-057J



AT-056J



APPLICATION AT-054J

Equipotential bars enable connection of various cables or round conductors with tin-plated copper connection terminals (for instance, AT-021K) carried out using 50 x 5 mm tape.

Reference	Denomination	Dimensions (mm)	Conductor connections	Material	Weight (kg)
AT-053J	Insulator	Ø36 x 51	M10 screw	Polyester	0.12
AT-150J	4 way earth bar	300 x 90 x 90	M10 screw	Copper	1.40
AT-054J	6 way earth bar	400 x 90 x 90	M10 screw	Copper	1.80
AT-116J	6 way earth bar	400 x 90 x 90	M10 screw	Stainless steel	1.00
AT-055J	6 way earth bar with single disconnecting link	475 x 90 x 96	M10 screw	Copper	2.30
AT-056J	6 way earth bar with twin disconnecting links	550 x 90 x 96	M10 screw	Copper	2.80
AT-057J	Disconnecting link	125 x 90 x 90	M10 screw	Copper	0.60
AT-058J	8 way earth bar	500 x 90 x 90	M10 screw	Copper	2.20
AT-117J	8 way earth bar	500 x 90 x 90	M10 screw	Stainless steel	1.20
AT-020J	8 way earth bar with single disconnecting link	575 x 90 x 96	M10 screw	Copper	2.70
AT-079J	8 way earth bar with twin disconnecting links	650 x 90 x 96	M10 screw	Copper	3.20
AT-090J	10 way earth bar	600 x 90 x 90	M10 screw	Copper	2.80
AT-118J	10 way earth bar	600 x 90 x 90	M10 screw	Stainless steel	1.40
AT-062J	10 way earth bar with single disconnecting link	675 x 90 x 96	M10 screw	Copper	3.30
AT-063J	10 way earth bar with twin disconnecting links	750 x 90 x 96	M10 screw	Copper	3.80
AT-064J	12 way earth bar	700 x 90 x 90	M10 screw	Copper	3.20
AT-119J	12 way earth bar	700 x 90 x 90	M10 screw	Stainless steel	1.60
AT-065J	12 way earth bar with single disconnecting link	775 x 90 x 96	M10 screw	Copper	3.70
AT-066J	12 way earth bar with twin disconnecting links	850 x 90 x 96	M10 screw	Copper	4.20
AT-067J	14 way earth bar	800 x 90 x 90	M10 screw	Copper	3.60
AT-068J	14 way earth bar with single disconnecting link	875 x 90 x 96	M10 screw	Copper	4.10
AT-069J	14 way earth bar with twin disconnecting links	950 x 90 x 96	M10 screw	Copper	4.60
AT-059J	16 way earth bar	900 x 90 x 90	M10 screw	Copper	4.00
AT-071J	16 way earth bar with single disconnecting link	975 x 90 x 96	M10 screw	Copper	4.50
AT-072J	16 way earth bar with twin disconnecting links	1050 x 90 x 96	M10 screw	Copper	5.00
AT-073J	18 way earth bar	1000 x 90 x 90	M10 screw	Copper	4.40
AT-074J	18 way earth bar with single disconnecting link	1075 x 90 x 96	M10 screw	Copper	4.90
AT-075J	18 way earth bar with twin disconnecting links	1150 x 90 x 96	M10 screw	Copper	5.40
AT-076J	20 way earth bar	1100 x 90 x 90	M10 screw	Copper	5.00
AT-077J	20 way earth bar with single disconnecting link	1175 x 90 x 96	M10 screw	Copper	5.50
AT-078J	20 way earth bar with twin disconnecting links	1250 x 90 x 96	M10 screw	Copper	6.00

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561