



> DOWN-CONDUCTORS AND ACCESSORIES


> TEST CLAMPS

> UNIVERSAL DISCONNECTING CLAMP FOR CABLE

Linear connection between cables.

Reference	Dimensions (mm)	Conductor range		Rod Ø (mm)	Material	Weight (g)
		Ø (mm)	mm ²			
AT-110F	50 x 30 x 20	8 - 10	50 - 70	-	Galvanized steel	180
AT-108F	50 x 30 x 20	8	50	-	Copper/Galvanized steel	180
AT-124F	50 x 30 x 20	8 - 10	50 - 70	-	Stainless steel	200
AT-113J	58 x 30 x 20	8 - 10 (Copper)	50 - 70 (Copper)	16 (Galvanized steel)	Copper/Galvanized steel	150
AT-114J	58 x 30 x 20	8 - 10	50 - 70	16	Galvanized steel	150
AT-115J	58 x 30 x 20	8 - 10	50 - 70	16	Stainless steel	100

Complies with UNE 21186, NF C 17-102, IEC 62305, IEC 62561



- AT-108F (Cu/GS - copper/galvanized steel)
- AT-110F (GS - galvanized steel)
- AT-124F (SS - stainless steel)



- APPLICATION AT-114J (GS - galvanized steel)
- AT-113J (Cu/GS - copper /galvanized steel)
- AT-115J (SS - stainless steel)